

## Highlights:

- null
- User friendly horizontal & vertical mounting
- PoE powered
- null
- null
- null
- null
- null
- null
- null

## Product information:

The RIVEA series is the AUDAC Touch™ configurable touchscreen range featuring a sleek and intuitive user interface designed for professional AV environments. Available with HD 7" or 10" glass front displays, the touchscreens combine elegant aesthetics with powerful performance. The anti-glare and anti-fingerprint finishing, together with the ultra-slim bezel and floating effect, ensure a refined appearance that seamlessly blends into any architectural setting.


Built on a completely new Linux platform, the RIVEA series delivers exceptional reliability, speed, and flexibility. Full AUDAC Touch™ dashboard support enables intuitive configuration, system monitoring, and control, while third-party control compatibility ensures easy integration within a wide range of automation systems.

The RIVEA series forms an extension of the network-controlled product range, while offering compatibility beyond this ecosystem. It can also operate in combination with Atellio and Consenso family products, as well as any device controllable through the AUDAC Touch™ application, ensuring unified system operation across different product families.

Equipped with proximity and ambient light sensors, RIVEA panels automatically adapt the display brightness and standby behavior for optimal user experience and energy efficiency. Designed for long-term scalability and modern aesthetics, the RIVEA series represents a future-ready control interface where design and performance meet.

## Applications:

- null
- Education
- Hotels
- null
- Residential



## Certification:

---



## Usage:

---



## System specifications:

---

Display	Size	null
	Type	IPS LCD display
	Resolution	1280 x 800 pixels
	Brightness	420 nits (cd/m <sup>2</sup> )±20
	Color Depth	24-bit
	Minimum viewing angle	80°/80°/80°/80° view angle (each direction)
Touch	Type	Multi touch capacitive touch panel (CTP)
	Interface Material	Glass
Sensors		Proximity Sensor
		Ambient Light Sensor
Buttons		Pin-hole
Connectors		1 x RJ45
Power	Supply	null
Temperature	Operating	32 - 104 °F

## Product Features:

---

Operating humidity		25% to 80% RH non-condensing
Colours		Black (RIVEA-M/B)
		White (RIVEA-M/W)
Dimensions		4.20 x 6.79 x 0.85 " (W x H x D)
	In-wall depth	0.20 "
	On-wall depth	0.66 "
Weight		0.75 lb

## Variants:

---

- RIVEA-M/B - Black version
- RIVEA-M/W - White version

PRELIMINARY