

Highlights:

- Stranded conductors
- Easy pulling capabilities
- null
- null
- null
- null

Product information:

The BLS207 are double isolated loudspeaker cables composed of two twisted conductors in a flexible PVC outer jacket. The double isolated construction allows the cable being used in public address (100V) audio systems while the smooth and durable outer jacket offers a great installers convenience for easy installation and pulling. The cable consist of individual isolated conductors with a section of 2 x 0.75 mm² (18 AWG) which are composed out of stranded copper clad aluminum (CCA) wires. The stranding keeps the cable flexible and easy to handle while the copper clad aluminum construction results in an electrical performance between copper and aluminum cables. It combines the advantages from two sides, such as solderability, lower weight and lower material cost than bare copper with the higher conductivity and higher strength than pure aluminum. The cable composition is made of 75% aluminum with 25% copper.



Properties:



Inner Conductors:



Product Features:

Application	null
Series	null

Physical Characteristics:

Type of cable	2-core loudspeaker cable		
Inner conductor	Material	CCA 24 x 0.2 mm (Ø)	
	Section	0.0012 "²	
	Number of conductors	2	
Insulation	Material	PVC 2.4 mm (Ø)	
	Colours	Red / Blue	
Separator	None		
Inner conductor	Audio	Conductor twisting	Lay length ≤ 60 mm
Outer jacket	Material	Flexible PVC 6.5 mm (Ø)	
	Colours	Black	
Inner conductor	American Wire Gauge	18 AWG	
	Conductor compositions	75 % Al - 25 % Cu	

Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006


Electrical Characteristics:

Max. conductor	DC resistance	37 (Ω / Km)
Dielectric strength	2 (KV / 1 min. DC)	

Mechanical Characteristics:

Temperature range	Fixed installation	- 68 °F till + 176 °F
	Mobile installation	- 59 °F till + 140 °F
Bending radius	Fixed installation	8 x outer diameter
	Mobile installation	10 x outer diameter

Cross sections:



Variants:

- BLS207/1 - 100 meter - black
- BLS207/3 - 300 meter - black