

CLS215C-B2CA

Loudspeaker cable - 2 x 1.5 mm² - 16 AWG - EN50399 CPR
Euroclass B2ca-s1a,d0,a1

Highlights:

- EN50399 CPR Euroclass B2ca-s1a,d0,a1
- 16 AWG (1.5 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant
- null
- null
- null
- null

Product information:


The CLS215C-B2ca series are 2-core installation loudspeaker cables compliant to the B2ca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire. In addition to its outstanding fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling.

The CLS2xx series consists of three models with individually LSHF isolated conductors in sections ranging from 1.5 mm² (16 AWG) up to 4 mm² (11 AWG) which are composed of stranded bare copper wires. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.


More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Product Features:

| | |
|-------------|------|
| Series | null |
| Application | null |

Physical Characteristics:

| | | |
|-----------------------|--------------------------|---------------------------|
| Type of cable | 2-core loudspeaker cable | |
| EN50399 CPR Euroclass | B2ca-s1a,d0,a1 | |
| Inner conductor | Material | BC 30 x 0.25 mm (Ø) (OFC) |
| | Section | 0.0023 "² |
| | Number of conductors | 2 |
| Insulation | Material | null |
| | Colours | Red / Blue |
| American Wire Gauge | 16 AWG | |
| Conductor twisting | Yes | |
| Filling | None | |
| Separator | None | |
| Outer jacket | Material | null |
| | Colours | Black |
| | | White |

Standards & regulations:

| | |
|------------------------|-------------------------------------|
| RoHS2 compliant | According EU Directive 2011/65/EU |
| Reach compliant | According EC 1907/2006 |
| Smoke emissions | According IEC 61034 |
| Zero halogen compounds | According EN 50267-2-1 IEC 60754 |
| Indoor / outdoor | UV resistant (UL1581, UVA, 720 h) |
| CPR Euroclass | B2ca-s1 a,d0,a1 |
| Flammability test | According EN 60332-1-2 |

Mechanical Characteristics:

| | | |
|-------------------|--------------------|------------------------|
| Temperature range | Fixed installation | - 68 °F till + 176 °F |
| UV resistant | | Yes |
| Bending radius | Fixed installation | > 7.5 x outer diameter |

Variants:

- CLS215C-B2CA/1 - 100 m wooden reel - Black
- CLS215CW-B2CA/1 - 100 m wooden reel - White
- CLS215C-B2CA/3 - 300 m wooden reel

Electrical Characteristics:

| | | |
|---------------------|---------------|----------------|
| Max. conductor | DC resistance | 1.33 Ω / 100 m |
| Dielectric strength | | null |
| Rated voltage | | 300 V |