

## Highlights:

---

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- 0.30 " (Ø) outer diameter
- Oxygen free copper
- Integrated stereo audio section
- Double Al-foil shielding

## Product information:

---

CLV115 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. A aluminium foil shielding will grant with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected. On one side, the mini jack cable end is 15 cm (projector side) and on the other side (computer side) the mini jack cable end is 50 cm.



## Components:

---

- CableType: SVGA215 - Audio + Video Cable

## Properties:

---



## Product Features:

---

Application	null
Series	null

## Physical Characteristics:

---

Inner conductor	Insulation	Material	FPE 1.55 mm (Ø)	
		Colours	White	
	Shielding	Aluminium foil	null	
		Drain wire	BC 7 x 0.12 mm (Ø) (OFC)	
	Audio	Insulation	Material	PE 7540 0.7 mm (Ø)
			Colours	Grey / Purple
		Shielding	Spiral	CCA 28 x 0.12 mm (Ø)
Overall shielding	Aluminium foil		null	
	Drain wire		BC 7 x 0.16 mm (Ø) (OFC)	
Outer jacket	Material		PVC 7.5 mm (Ø)	
	Colours		Black	
Type of cable			75 Ω VGA video cable	
Inner conductor	Material		BC 7 x 0.12 mm (Ø) (OFC)	
	Audio	Material	BC 10 x 0.12 mm (Ø) (OFC)	
Filling			Cotton Yarn	
Inner conductor	American Wire Gauge		28 AWG	
Fitted connectors			SVGA male	

## Variants:

---

- CLV115/15 - 15 meter
- CLV115/20 - 20 meter
- CLV115/25 - 25 meter
- CLV115/30 - 30 meter