



Highlights:

- 24 AWG thin and dense stranded conductors
- Highflex™ solid & flexible jacket
- 0.24 " (Ø) outer diameter
- null

Product information:


The PMI224 is a high-quality microphone cable with a highly flexible outer jacket. This cable is made rigid, which allows you to roll it up, even at longer lengths effortlessly. Two 24 AWG (0.22 mm²) conductors consisting of 12 copper strands with 0.15 mm thickness are surrounded by an 80-strand braided copper shielding with superior coverage. Combined with the thick and soft PVC outer jacket, this provides a flexible but solid feel while allowing it to withstand an extreme amount of bending cycles. Optimal signal transmission is guaranteed due to the low capacitance and use of high-purity copper, while the high-coverage shielding provides excellent immunity against interference. These features make the PMI224 perfect for use in professional stage & studio applications.



Certification:



Properties:



Inner Conductors:



Shielding:



Product Features:

| | |
|-------------|------|
| Application | null |
| Series | null |

Physical Characteristics:

| | | | |
|-----------------|----------------------|----------|-------------------------------|
| Inner conductor | Insulation | Material | PE 1.5 mm (Ø) |
| | | Colours | White / Red |
| | Shielding | Braiding | BC 16 x 5 x 0.10 mm (Ø) (OFC) |
| Outer jacket | Material | | Highflex PVC 6.2 mm (Ø) |
| | Colours | | Black |
| Type of cable | | | 24 AWG Microphone cable |
| Inner conductor | Material | | BC 12 x 0.15 mm (Ø) (OFC) |
| | Section | | 0.00034 "2 |
| Filling | | | Cotton Yarn |
| Inner conductor | Number of conductors | | 2 |
| | Conductor twisting | | Yes |

Mechanical Characteristics:

| | | |
|-------------------|---------------------|-----------------------|
| Temperature range | Fixed installation | - 68 °F till + 158 °F |
| | Mobile installation | - 41 °F till + 158 °F |
| Bending radius | Fixed installation | 5 x outer diameter |
| | Mobile installation | 10 x outer diameter |

Variants:

- PMI224/1 - 100 meters
- PMI224/3 - 300 meters