

### Highlights:

---

- Highflex™ solid & flexible jacket
- 2.5 mm<sup>2</sup> (13 AWG) thin and dense stranded conductors
- 0.43 " (Ø) outer diameter
- Oxygen free copper
- Neutrik NL4FXX-W-S connectors by Neutrik
- null

### Product information:

---

The PRA524 is a high quality loudspeaker cable constructed using the PLH425 cable and fitted with two Neutrik 4 pole speakON cable (NL4FXX-W-S) conductors. The cable consists of four 2.5 mm<sup>2</sup> (13 AWG) thin and dense stranded conductors. The combination of thin and dense strands with high purity oxygen free copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket of 11 mm provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding Rental & MI applications. An attached shrink sleeve allows custom labeling for easy identification. The cable comes in different lengths from 1.5 meters to 20 meters.



### Components:

---

- Connector: NL4FXX-W - Neutrik speakON 4 pole cable connector



### Certification:

---



### Properties:

---



### Product Features:

---

Series	null
Application	null

## Physical Characteristics:

---

Type of cable	4-core loudspeaker cable		
Inner conductor	Material	BC 224 x 0.12 mm (Ø) (OFC)	
	Section	0.0039 "²	
Insulation	Material	PVC 3.2 mm (Ø)	
	Colours	Black / Red / Blue / Yellow	
Number of conductors	4		
	American Wire Gauge	13 AWG	
Fitted connectors	null		
Connection type	SpeakON Female to Female		
Outer jacket	Material	Durable PVC 11 mm (Ø)	
	Colours	Black	

## Mechanical Characteristics:

---

Temperature range	Fixed installation	- 68 °F till + 158 °F
	Mobile installation	- 41 °F till + 158 °F
Bending radius	Fixed installation	5 x outer diameter
	Mobile installation	10 x outer diameter

## Electrical Characteristics:

---

Lead resistance	0.8 Ω / 100 m
-----------------	---------------

## Variants:

---

- PRA524/1.5 - 1.5 meter
- PRA524/3 - 3 meters
- PRA524/5 - 5 meter
- PRA524/10 - 10 meter
- PRA524/15 - 15 meter
- PRA524/20 - 20 meter